

| GFX <sup>1,2,3</sup><br>MODEL<br>(.pdf) | DRAIN<br>IN/OUT<br>(DWV) | COLD<br>IN/OUT<br>Type-L | LOA<br>(in.)      | DHR <sup>4</sup><br>EFF. | PRESS<br>DROP<br>(PSI) | SHIP<br>WGT<br>(LBS) | SAMPLE APPLICATIONS  |
|---|--------------------------|--------------------------|-------------------|--------------------------|------------------------|----------------------|--|
| <a href="#">G3-60</a>                   | 3" & 3"                  | 1/2"                     | 60                | 60%                      | 8                      | 49                   | Single Bathroom Homes, Industrial Cooling-Walls<br>Hydronic Heating            |
| <a href="#">G3-40</a>                   | 3" & 3"                  | 1/2"                     | 40                | 49%                      | 5                      | 32                   | Restricted Height Location   |
| <a href="#">G3-30</a>                   | 3" & 3"                  | 1/2"                     | 30                | 41%                      | 4                      | 24                   | Restricted Height Location   |
| <a href="#">G4-60</a>                   | 4" & 4"                  | 1/2"                     | 60                | 67%                      | 11                     | 64                   | Single Bathroom Homes, Industrial Cooling-Walls<br>Hydronic Heating            |
| <a href="#">G4-40</a>                   | 4" & 4"                  | 1/2"                     | 40                | 56%                      | 7                      | 40                   | Restricted Height Location   |
| <a href="#">G4-30</a>                   | 4" & 4"                  | 1/2"                     | 30                | 48%                      | 5                      | 31                   | Restricted Height Location   |
| <a href="#">S3-60</a>                   | 3" & 3"                  | 3/4"                     | 60                | 57%                      | <2                     | 49                   | Whole House Model, Hi-Flo Pressure Drop 1/6 <sup>th</sup> G3-60                |
| <a href="#">S3-40</a>                   | 3" & 3"                  | 3/4"                     | 40                | 47%                      | <2                     | 32                   | Restricted Height Location   |
| <a href="#">S3-30</a>                   | 3" & 3"                  | 3/4"                     | 30                | 39%                      | <2                     | 24                   | Restricted Height Location   |
| <a href="#">S4-60</a>                   | 4" & 4"                  | 3/4"                     | 60                | 62%                      | <3                     | 64                   | Whole House Model, Hi-Flo Pressure Drop 1/6 <sup>th</sup> G4-60                |
| <a href="#">S4-40</a>                   | 4" & 4"                  | 3/4"                     | 40                | 53%                      | <2                     | 40                   | Restricted Height Location   |
| <a href="#">S4-30</a>                   | 4" & 4"                  | 3/4"                     | 30                | 46%                      | <2                     | 31                   | Restricted Height Location   |
| <a href="#">P3-60</a>                   | 2" & 3"                  | 3/4"                     | 60<br>1/8         | 74%                      | <3                     | 105                  | Commercial Dishwashers, Beauty Shops, Gang Showers, etc.                       |
| <a href="#">P3-40</a>                   | 2" & 3"                  | 3/4"                     | 46 <sup>1/4</sup> | 64%                      | <3                     | 55                   | Restricted Height Location   |
| <a href="#">P3-30</a>                   | 2" & 3"                  | 3/4"                     | 35 <sup>1/4</sup> | 56%                      | <2                     | 49                   | Restricted Height Location   |
| <a href="#">P4-60</a>                   | 2" & 4"                  | 3/4"                     | 60 <sup>1/8</sup> | 66% (4.5<br>gpm)         | 10                     | 111                  | Commercial Dishwashers, Beauty Shops, Gang Showers, etc.                       |
| <a href="#">P2S4-40</a>                 | 2" & 4"                  | 3/4"                     | 80                | 70% (4.5<br>gpm)         | <2                     | 155                  | Two pairs of S4-40's with 80" drains connected in parallel;<br>coils in series |

Coil & drain flow rates are 2.25 gpm unless specified otherwise.

<sup>1</sup> G Models - 1/2" Type-L coils on Type-DWV copper tube.

<sup>2</sup> S Models - two 1/2" Type-L coils manifolded on single Type-DWV copper tube

<sup>3</sup> P & M2P Models are "G" or "S" models manifolded together.

<sup>4</sup> Nominal Drainwater Heat Recovery (DHR) Efficiency for balanced flow near 2.25 gallons per minute (gpm)

<sup>5</sup> Nominal effectiveness for coil flow rate of 1 gpm and a flooded-tube flow-rate greater than 5 gpm

Non-standard models having 3 or more coils on single 2", 3" or 4" copper or stainless tubing is available upon request

| <b>GFX**<br/>MODEL<br/>(.pdf)</b> | <b>DRAIN<br/>IN/OUT<br/>(DWV)</b> | <b>COLD<br/>IN/OUT<br/>Type-L</b> | <b>LOA<br/>(in.)</b> | <b>DHR***<br/>EFF.</b>                      | <b>PRESS DROP<br/>(PSI)</b>           | <b>SHIP<br/>WGT<br/>(LBS)</b> | <b>SAMPLE APPLICATIONS</b>  |
|-----------------------------------|-----------------------------------|-----------------------------------|----------------------|---|---------------------------------------|-------------------------------|---|
| <a href="#">P2S3-40</a>           | 2" & 4"                           | 3/4"                              | 80                   | 64%<br>(4.5 gpm)                            | <2                                    | 135                           | Two pairs of S3-40's with 80" drains connected in parallel; coils in series |
| <a href="#">PS4-60</a>            | 2" & 4"                           | 1"                                | 60 <sup>1/8</sup>    | 62%<br>(4.5 gpm)                            | <2                                    | 116                           | Two Manifoldd S4-60 GFX's Hi-Flo Pressure Prop ~/6 <sup>th</sup> P4-60      |
| <a href="#">M2P4-60</a>           | 2" & 4"                           | 1"                                | 60 <sup>1/8</sup>    | 79%<br>(4.5 gpm)                            | <2                                    | 235                           | Two P4-60's With 1 Drain & 2 Cold In/Out Water Manifolds                    |
| <a href="#">G3-60-3</a>           | 3" & 3"                           | 3/4"                              | 60                   | 50, 40,<br>24%<br>@ 2.25,<br>4.5 & 9<br>gpm | 0.7, 1.6, 4.4<br>@ 2.25, 4.5 &<br>gpm | 53                            | 3-coil Special For Troutdale Terrace Apartment Project                      |
| <a href="#">G4-80-4</a>           | 4" & 4"                           | 1"                                | 79 <sup>7/8</sup>    | 63, 52,<br>38%<br>@ 2.25,<br>4.5 & 9<br>gpm | 0.5, 1.2, 3.3<br>@ 2.25, 4.5 &<br>gpm | 64                            | 4-coil Special For New Jersey Apartment Project                             |
| <a href="#">S2-60</a>             | 2                                 | 1/2"                              | 60                   | 49%   | <3.5                                  | 35                            | 2-coil Special For Troutdale Terrace Project in Troutdale, OR               |
| <a href="#">G2-30</a>             | 2                                 | 1/4"                              | 30                   | 33%   | <9                                    | 15                            | Crawl Spaces, Single Shower, Under Sinks, Ice Machines, etc.                |
| <a href="#">G2-24</a>             | 2                                 | 1/4"                              | 24                   | 28%   | <7                                    | 12                            |   |
| <a href="#">G2-20</a>             | 2                                 | 1/4"                              | 20                   | 24%   | <6                                    | 10                            |   |
| <a href="#">G2-12</a>             | 2" (Type L)                       | 1/4"                              | 12                   | 13.5% <sup>5</sup> (1;<br>>5 gpm)           | 0.7                                   | 3                             | Tap heat off hot water recirc- loop to eliminate inline water               |
| <a href="#">G1.5-12</a>           | 1.5" (Type L)                     | 1/4"                              | 12                   | 10.3% <sup>5</sup> (1;<br>>5 gpm)           | 0.7                                   | 3                             | Heaters & save water by providing instant hot water.                        |

**Plumbing Code 3 step process** to meet or exceed federal, state and local plumbing codes

1. 3<sup>rd</sup> party certified to meet safety standards set forth by UL, ETL, and IAPMO.
2. Constructed with lead free materials incised in accordance with NSF-61 to meet Safe Drinking Water Act specifications.
3. Crafted without soldering or brazing the coil to the drain pipe to meet specifications of an all copper vented double-walled heat exchanger safe for all potable water systems.

Prices and models are subject to change without notice